

1 2 3 4 5 6


A

B


C

D


- 01 Blue
- 02 Orange
- 03 Green
- 04 Brown
- 05 Gray
- 06 White
- 07 Red
- 08 Black
- 09 Yellow
- 10 Purple
- 11 Pink
- 12 Aqua



- 01 Blue
- 02 Orange
- 03 Green
- 04 Brown
- 05 Gray
- 06 White
- 07 Red
- 08 Black
- 09 Yellow
- 10 Purple
- 11 Pink
- 12 Aqua



LC Connector (SCALE 1/1)



Cable Section (SCALE 5/1)

A

B

C

D

1 2 3 4 5 6 0 3 4 10cm 5 6

ACT

Drawn by : YMN

ACT Multimode Fiber Optic Indoor / Outdoor cable 50/125 OM3

Item : RL46xx-B2ca

Revision : 1.0

Date : 04-07-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only.
This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions.
Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.

Specifications Installation cable (A)	
Type	Indoor/Outdoor cable
Outer diameter	6.5mm
Tensile strength	350N
Operation temp.	-20°C to +70°C
Storage temp.	-40°C to +80°C
Outer Jacket	LSZH
Euro fire class	B2ca s1, d1, a1
Cable colour	Black
UV resistance	Yes
Cable printing	CE MM/YY ACT 12F 50/125 OM3 10280010 xxxxM DoP: 1320-2231 B2ca, s1, d1, a1 NB0598 Communications supply in-/outdoor (MM=month, YY=year)
Specifications Heat Shrink Tubing (B,C)	
Length	80mm
Specifications Fanout cable (D,E)	
Type	Tubing
Outer diameter	0.9mm
Operation temp.	-20°C to +70°C
Storage temp.	-40°C to +80°C
Colors	Blue, Orange, Green, Brown, Gray, White, Red, Black, Yellow, Purple, Pink, Aqua
Fanout length	500mm (+50mm-0mm) - 940mm (+50mm-0mm)
Fanout staggered increments	40mm
Specifications Connector (F,G)	
Connector	LC
Polishing Connector	UPC
Ferrule Connector	Ceramic Zirconia (ZrO2)
Ferrule Diameter	1.25mm
Housing	Ivory (PC)
Boot	White (TPV)
Cap	White (PE)



ACT Multimode Fiber Optic Indoor / Outdoor cable 50/125 OM3



Item : RL46xx-B2ca

Revision : 1.0

Date : 04-07-2024

Drawn by : YMN

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only.
This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions.
Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.



Item	Length(m)	Item	Length(m)
RL4601	10	RL4616	160
RL4602	20	RL4617	170
RL4603	30	RL4618	180
RL4604	40	RL4619	190
RL4605	50	RL4620	200
RL4606	60	RL4621	210
RL4607	70	RL4622	220
RL4608	80	RL4623	230
RL4609	90	RL4624	240
RL4610	100	RL4625	250
RL4611	110	RL4626	260
RL4612	120	RL4627	270
RL4613	130	RL4628	280
RL4614	140	RL4629	290
RL4615	150	RL4630	300

Specifications heat shrink tubing (1)	
Length	60mm
Specifications protective tube (2)	
Material	PVC
Color	Transparent
Dimensions	1120mm(+50mm -0mm) x 12mm x 15mm

Length (m)	Reel Weight (KG)	Reel dimension (mm)
120	1.7	327 (H) x 345 (ø)
121-240	1.9	327 (H) x 400 (ø)
241-330	2.8	330 (H) x 450 (ø)
331-420	3.1	330 (H) x 480 (ø)
≥421	3.3	400 (H) x 480 (ø)

	ACT Multimode Fiber Optic Indoor / Outdoor cable 50/125 OM3	
	Item : RL46xx-B2ca	Revision : 1.0
		Date : 04-07-2024
Drawn by : YMN	This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.	

1	2	3	4	5	6																			
A						A																		
B	<table><tr><th colspan="2">Specifications fiber</th></tr><tr><td>Fiber type</td><td>Multimode</td></tr><tr><td>Fiber class</td><td>OM3</td></tr><tr><td>Diameter core / cladding</td><td>50/125</td></tr></table>					Specifications fiber		Fiber type	Multimode	Fiber class	OM3	Diameter core / cladding	50/125	B										
	Specifications fiber																							
	Fiber type	Multimode																						
	Fiber class	OM3																						
Diameter core / cladding	50/125																							
C	<table><tr><th colspan="2">Specifications optical performance</th></tr><tr><td>Insertion Loss (IL) typical</td><td>0.1 dB</td></tr><tr><td>Insertion Loss (IL) maximum</td><td>0.15 dB</td></tr><tr><td>Return Loss (RL)</td><td>≥ 35 dB</td></tr></table>					Specifications optical performance		Insertion Loss (IL) typical	0.1 dB	Insertion Loss (IL) maximum	0.15 dB	Return Loss (RL)	≥ 35 dB	C										
	Specifications optical performance																							
	Insertion Loss (IL) typical	0.1 dB																						
	Insertion Loss (IL) maximum	0.15 dB																						
Return Loss (RL)	≥ 35 dB																							
D	<table><tr><th colspan="2">Standard compliances</th></tr><tr><td>IEC 61754-20</td><td>Fibre optic connector interfaces - Type LC connector family</td></tr><tr><td>IEC 61300-3-47</td><td>Examinations and measurements - End face geometry of PC/APC spherically polished ferrules using interferometry</td></tr><tr><td>IEC 60794-2-20</td><td>Indoor cables - Family specification for multi-fibre optical cables</td></tr><tr><td>IEC 60794-1-2</td><td>Basic optical cable test procedures</td></tr><tr><td>IEC 60332-1-2</td><td>Test for vertical flame propagation for a single insulated wire or cable</td></tr><tr><td>IEC 60754-1</td><td>Determination of the halogen acid gas content</td></tr><tr><td>IEC 60754-2</td><td>Determination of acidity (by pH measurement) and conductivity</td></tr><tr><td>IEC 61034-2</td><td>Measurement of smoke density of cables burning under defined conditions</td></tr></table>					Standard compliances		IEC 61754-20	Fibre optic connector interfaces - Type LC connector family	IEC 61300-3-47	Examinations and measurements - End face geometry of PC/APC spherically polished ferrules using interferometry	IEC 60794-2-20	Indoor cables - Family specification for multi-fibre optical cables	IEC 60794-1-2	Basic optical cable test procedures	IEC 60332-1-2	Test for vertical flame propagation for a single insulated wire or cable	IEC 60754-1	Determination of the halogen acid gas content	IEC 60754-2	Determination of acidity (by pH measurement) and conductivity	IEC 61034-2	Measurement of smoke density of cables burning under defined conditions	D
	Standard compliances																							
	IEC 61754-20	Fibre optic connector interfaces - Type LC connector family																						
	IEC 61300-3-47	Examinations and measurements - End face geometry of PC/APC spherically polished ferrules using interferometry																						
	IEC 60794-2-20	Indoor cables - Family specification for multi-fibre optical cables																						
	IEC 60794-1-2	Basic optical cable test procedures																						
	IEC 60332-1-2	Test for vertical flame propagation for a single insulated wire or cable																						
	IEC 60754-1	Determination of the halogen acid gas content																						
	IEC 60754-2	Determination of acidity (by pH measurement) and conductivity																						
IEC 61034-2	Measurement of smoke density of cables burning under defined conditions																							
			<table><tr><td rowspan="3"></td><td colspan="2">ACT Multimode Fiber Optic Indoor / Outdoor cable 50/125 OM3</td></tr><tr><td rowspan="2">Item : RL46xx-B2ca</td><td>Revision : 1.0</td></tr><tr><td>Date : 04-07-2024</td></tr><tr><td>Drawn by : YMN</td><td colspan="2">This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.</td></tr></table>				ACT Multimode Fiber Optic Indoor / Outdoor cable 50/125 OM3		Item : RL46xx-B2ca	Revision : 1.0	Date : 04-07-2024	Drawn by : YMN	This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.											
	ACT Multimode Fiber Optic Indoor / Outdoor cable 50/125 OM3																							
	Item : RL46xx-B2ca	Revision : 1.0																						
		Date : 04-07-2024																						
Drawn by : YMN	This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.																							
1	2	0	3	4	5	6																		



Drawn by : YMN

ACT Multimode Fiber Optic Indoor / Outdoor cable 50/125 OM3

Item : RL46xx-B2ca

Revision : 1.0

Date : 04-07-2024

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.

0

3

4

10cm

5

6